



MODEL 82	A	B	C	MODEL 82	A	B	C
MAGNET	12	1.75	2.9	STRIKE	10	2.75	.5

## ELECTROMAGNETIC LOCK – Model 82B

### Features

- 1,800 pounds of pull-apart holding force
- Lifetime replacement warranty
- Power consumption of 350mA @ 12VDC & 200mA @ 24VDC – 4 Watts
- Automatic dual voltage, 12 VDC or 24 VDC, no field adjustment required
- Bondstat standard
- Instant release circuit, no residual magnetism
- Surface mounts using only a drill and allen wrench
- Fully sealed electronics, tamper proof & weather proof
- Mounted using steel machine screws into blind finishing nuts
- Architectural brushed stainless steel finish
- Polished brass, clear anodized, & polished stainless finish dress covers available
- Hardware accessories include brackets, housings, and dress covers as needed for every opening type
- Ten feet of jacketed stranded conductor
- Lock and strikes plated to provide corrosion resistance
- Fail Safe
- UL listed



### Options

- Bondstat – Lock status “Form C” contacts to monitor status of the lock
- DPS Door Status – Integrated door sensing reed switch with built in resettable polyswitch
- Face Mount – Mounting holes on the face of the lock for mounting on inswing doors and gates
- Conduit fitting
- Offset Strike
- Split Strike