



## ► QuadraFlare® | Perimeter Lights

### FEATURES

- Advanced Solaris LED reflector technology.
- Available in 6x4, 7x3, and 9x7 models.
- 9x7 models feature unique Quad-X patterns.
- LEDs available in Amber, Blue, Green, Red or White.
- Available with built-in flasher featuring a variety of selectable patterns.
- Optional chrome-plated trim bezel.
- Surpasses NFPA and GSA K-spec compliant upper and lower level requirements.
- Brake/Tail/Turn, Turn Arrow and Back-up light models available in 6x4.

### APPROVALS

- QuadraFlare 6x4, 7x3, and 9x7 lights: NFPA 1901, GSA K-spec
- Brake/Tail/Turn/Back-up lights: FMVSS-108, SAE J2040, SAE 2261, and SAE J593

#### QuadraFlare 6x4, 7x3 and 9x7 Lights

Federal Signal QuadraFlare LED lights are designed with the Solaris® LED reflector technology for superior off-axis lighting. These LED exterior lights are engineered to surpass NFPA and GSA Triple-K specifications for upper and lower level requirements and carry a five-year LED warranty.

QuadraFlares are available in 6x4, 7x3, and 9x7 standard models. Therefore, no special die-cut is required to the body of your fire truck or ambulance. Models are available with an optional chrome-plated trim bezel for a traditional finish. All models offer a built-in flasher featuring a variety of selectable patterns. In addition, the 9x7 models feature unique Quad-X patterns for attention-getting warning.

#### QuadraFlare Brake/Tail/Turn/Back-up Lights

These assemblies house Federal Signal's 6x4 QuadraFlares. QuadraFlares are designed with the Solaris® LED reflector technology for superior off-axis lighting. The exterior LED lights are available in 3-position vertical, 3-position horizontal, and 4-position vertical chrome-plated castings. No special die-cut is required to the body of your fire truck or ambulance. All LEDs carry a five-year warranty.



- A Quad Window – Fresnel lens with enhanced design provides outstanding performance to meet various industry lighting specifications.
- B SOLARIS™ Reflector –Engineered to capture more light and features four scalloped quadrants for customized flash patterns.
- C PC Board Design – Uniquely manufactured PC boards incorporate LEDs onto the surface providing fewer connections for increased reliability. The board also acts a heat sink to allow maximum LED output.
- D Push-button Pattern Selection – Easy to access pattern control button located directly on the PC board.
- E Gore-Tex Gasket – Allows the unit to breathe, eliminating condensation and water retention.
- F Surface Mount – QuadraFlare LED warning lights are designed to be surface mounted, eliminating the need to cut holes into the vehicle body.

### Five Pattern Arrangements In One Model!

QuadraFlare LED perimeter lights contain a built-in flasher and maybe used with an external flasher or multiplex system by using a “steady on” pattern. Solaris reflectors and our unique software configuration provide a variety of flash patterns and functionality. The unique quad reflector design allows for horizontal, vertical and our unique X-Quad flash patterns.



1. “Steady-on” may apply external flasher (all QuadraFlare styles)

2. Full Flash (all QuadraFlare styles)



3. Vertical flash pattern (6x4 and 9x7 styles)



4. Horizontal flash pattern (7x3 and 9x7 styles)



4. Quad-X flash pattern (9x7 style only)



## SPECIFICATIONS

### Specifications

Model Family	Current Draw*	Input Voltage	Operating Temperature	Physical Specifications H x W x L	Ship Weight
All QL64 Models	Max 2.0A	12.8 VDC	-40°C-+65°C	4.2 in x 6.6 in x 1.5 in (10.7 cm x 16.7 cm x 3.8 cm)**	1.8 lbs (0.8 kg)
All QL73 Models	Max 2.0A	12.8 VDC	-40°C-+65°C	7.4 in x 3.2 in x 1.7 in (18.7 cm x 8.0 cm x 4.3 cm)**	1.0 lbs (0.5 kg)
All QL97 Models	Max 4.0A	12.8 VDC	-40°C-+65°C	7.2 in x 9.2 in x 1.7 in (18.3 cm x 23.4 cm x 4.3 cm)**	2.0 lbs (0.9 kg)
QL64Z3V-LED	Max 2.5A	12.8 VDC	-40°C-+65°C	15.1 in x 7.4 in x 1.6 in (38.4 cm x 18.8 cm x 4.1 cm)	11.0 lbs (5.0 kg)
QL64Z3V-Left/Right	Max 2.5A	12.8 VDC	-40°C-+65°C	15.1 in x 7.4 in x 1.6 in (38.4 cm x 18.8 cm x 1.6 cm)	11.0 lbs (5.0 kg)
QL643H-LED	Max 2.5A	12.8 VDC	-40°C-+65°C	5.0 in x 22.3 in x 1.6 in (12.7 cm x 56.6 cm x 4.1 cm)	11.0 lbs (5.0 kg)
QL643H-Left/Right	Max 2.5A	12.8 VDC	-40°C-+65°C	5.0 in x 22.3 in x 1.6 in (12.7 cm x 56.6 cm x 4.1 cm)	11.0 lbs (5.0 kg)
QL64Z4V-LED	Max 4.0A	12.8 VDC	-40°C-+65°C	19.6 in x 7.4 in x 1.6 in (49.8 cm x 18.8 cm x 4.1 cm)	12.5 lbs (5.7 kg)
QL64Z4V-Left/Right	Max 4.0A	12.8 VDC	-40°C-+65°C	19.6 in x 7.4 in x 1.6 in (49.8 cm x 18.8 cm x 4.1 cm)	12.5 lbs (5.7 kg)

\* Current draw rated at “steady on.” During normal operations, amp draw of flashing lights may be as much as 50% lower than stated amount.

\*\* Without trim bezel.

Select Model

**Warning Lights**

Model #	LED Color	Lens Color	LED Count	Internal Flasher	Split LED	Dimming
<b>6x4 QuadraFlares</b>						
QL64-(color)	amber, blue, white, green	amber, blue, clear, green	12	YES		YES
QL64-R	red	red	16	YES		YES
QL64C-(color)	amber, blue, red, white, green	clear	12	YES		YES
QL64C-RR	red	clear	16	YES		YES
QL64C-(color)(color)	amber, blue, red, white, green	clear	10	YES	YES	YES
<b>7X3 Quadraflares</b>						
QL73XF-(color)	amber, blue, red, white, green	amber, blue, red, clear, green	8	YES		YES
QL73XFC-(color)	amber, blue, red, white, green	clear	8	YES		YES
QL73SF-(color)(color)*	amber, blue, red, green	amber, blue, red, clear, green	8	YES	YES	YES
QL73SFC-(color)(color)	amber, blue, red, white, green	clear	8	YES	YES	YES
<b>9x7 Quadraflares</b>						
QL97XF-(color)	amber, blue, red, white, green	amber, blue, red, clear, green	16	YES		YES
QL97XFC-(color)	amber, blue, red, white, green	clear	16	YES		YES
QL97SF-(color)(color)*	amber, blue, red, green	amber, blue, red, clear, green	16	YES	YES	YES
QL97SFC-(color)(color)	amber, blue, red, white, green	clear	16		YES	YES

**Brake / Tail / Turn / Backup / LED warning lights**

Model #	LED Description	Lens Color
QL64-BTT	Brake/Tail/Turn, red LED	red
QL64-ARROW	Turn Arrow, amber LED	amber
QL64-TURN	Turn light, amber LED	amber
QL64-BACKUP	Backup light, white LED	clear
QL64Z3V-(LEFT or RIGHT)	Installed QL64-BTT, QL64-ARROW, QL64-BACKUP	red/amber,clear
QL64Z3V-LED	Installed QL64-BTT, QL64-TURN, QL64-BACKUP	red/amber,clear
QL64Z3H-(LEFT or RIGHT)	Installed QL64-BTT, QL64-ARROW, QL64-BACKUP	red/amber,clear
QL64Z3H-LED(LEFT or RIGHT)	Installed QL64-BTT, QL64-TURN, QL64-BACKUP	red/amber,clear
QL64Z4V-(LEFT or RIGHT)	Installed QL64-BTT, QL64-ARROW, QL64-BACKUP, QL64-R	red/amber,clear,red
QL64Z4V-LED	Installed QL64-BTT, QL64-TURN, QL64-BACKUP, QL64-R	red/amber,clear,red

**Mounting Options**

Model #	LED Description	Size
QL64MC	Trim Bezel, chrome, gasket	6" x 4"
QL64MB	Trim Bezel, black, gasket	6" x 4"
QL64MHL	Headlight mount kit	6" x 4"
QL97MC	Trim Bezel, chrome, gasket	9" x 7"
QL97MB	Trim Bezel, black, gasket	9" x 7"
QL73MC	Trim Bezel, chrome, gasket	7" x 3"
QL73MB	Trim Bezel, black, gasket	7" x 3"
QL64Z3V	3 postion, vertical casting, gasket, hardware only	6" x 4"
QL64Z3H	3 postion, horizontal casting, gasket, hardware only	6" x 4"
QL64Z3V	4 postion, vertical casting, gasket, hardware only	6" x 4"

\* Single color split LEDs. Example: red/red LEDs, red lens.



QuadraFlare and Solaris are trademarks of Federal Signal Corporation.  
Gore-Tex is a registered trademark of W. L. Gore and Associates.

©2016 Federal Signal Corporation. M4190 I 216