



RMCARD305 Remote Management Card

Remotely manage, monitor and control your UPS from a web browser or SNMP management application.

The CyberPower RMCARD305 is a full-featured network UPS management device that remotely manages, monitors, and controls the Online Series UPS systems.

The internal card allows remote monitoring and control of a UPS via Web Browser, CLI, or NMS connection. By utilizing the auto-shutdown PowerPanel Business Edition software, servers and workstations stay protected from data loss due to power failure. An optional Environmental Sensor (ENVIROSENSOR) can be added to monitor ambient temperature and humidity.

The firmware can be updated by users to insure you have the latest features and updates. TLS security management is also provided to protect the integrity of the network.

A Three-Year Warranty ensures that this network management card has passed our highest quality standards in design, assembly, material, and workmanship.

Features

- Real time UPS monitoring
- Supports optional environment sensor management
- Remote management and configuration of UPS via Web Browser, CLI (Telnet or SSH), or NMS (SNMPv1 or v3)
- Automatic events notification via Email, SMS, SNMP Traps, and Syslog
- Logging of UPS Events and Status Records
- Support TCP/IP, UDP, SNMP v1 and v3, NTP, DNS, SMTP, IPv4 and v6, SSH, RADIUS, TLS, LDAP, LDAPS, Syslog, Windows Active Directory, CLI, and Secure FTP
- User upgradeable firmware
- Allows configuration and updating of multiple units at once
- Compatible with select Smart App Online models*

RMCARD305 Remote Management Card

Remotely manage, monitor and control your UPS from a web browser or SNMP management application.

GENERAL	
Type	Network Management Card
COMMUNICATION	
Protocols	TCP/IP, UDP, SNMP v1 and v3, NTP, DNS, SMTP, IPv4 and v6, SSH, RADIUS, TLS, LDAP, Syslog, Windows Active Directory, CLI, and Secure FTP
Network Connection	RJ45 - 10/100Mbps Ethernet
PHYSICAL	
Dimensions (WxHxD) (in.)	2.6 x 1.7 x 5.3
Dimensions (WxHxD) (mm.)	66.04 x 43.18 x 134.62
Weight (lbs.)	0.2
Weight (kg.)	0.09
SHIPPING DIMENSIONS	
Dimensions (WxHxD) (in.)	6.8 x 2.4 x 6.5
Dimensions (WxHxD) (mm.)	172.72 x 60.96 x 165.1
Weight (lbs.)	0.4
Weight (kg.)	0.18
ENVIRONMENTAL	
Operating Temperature	32°F to 104°F / 0°C to 40°C
Operating Humidity	0% - 90% non-condensing
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	14°F to 122°F / -10°C to 50°C
Storage Relative Humidity	0% - 95% non condensing
Storage Elevation	0-50000 feet (0-15000 meters)
COMPATIBILITY	
UPS Models	Online Series UPS with Smart Slot*
CERTIFICATIONS	
Safety	FCC Class A, CE
Environmental	RoHS Compliant
WARRANTY	
Product Warranty	3 Years Limited