


LMR BATTERY SPECIFICATIONS	PART NUMBER
	BP4448LI

COMPATIBLE RADIOS	Motorola APX1000, APX3000, APX4000, XPR3300, XPR3300e, XPR3500, XPR3500e, XPR7350, XPR7350e, XPR7550, XPR7550e, XPR7580, XPR7580e, DP4400, DP4401, DP4600, DP4601, DP4800, DP4801
REPLACES OEM BATTERY	PMNN4448
COMPATIBLE CHARGERS	Endura EC1-MT16A, EC1M-MT16A, EC2M-MT16-D, EC6M-MT16A, EC12M-MT16-D / Logic LEVCA-MT16
VOLTAGE	7.2V
CAPACITY	2900 mAh / 20.4 Wh
CHEMISTRY	Li-Ion
CELL TYPE	Panasonic or equivalent
OPERATING TEMPERATURE	-20° C to +60° C (discharge) / 0° C to +40° C (charge)
CHARGE CYCLES	>300
CHARGE TYPE	Rapid
CONDITIONER COMPATIBLE	Non-smart battery, "safe charges" on Motorola IMPRES desktop chargers, but is not conditioned (conditioning not required to maintain cycle life or battery run time)
PROTECTION TYPES	Over-charge / over-discharge / over-temperature
HOUSING MATERIAL / SEAL	ABS / ultrasonic weld
INGRESS RATING	IP67
METAL WELDING	Pure nickel tabs w/ spot welder
CLIP	Included
WARRANTY	12 months
PRODUCT PHOTO	 <div style="border: 1px dashed black; padding: 5px; display: inline-block; margin-left: 20px;"> Dimensions (HxWxD): 4.51" x 2.18" x 0.91" </div>