

# Service Lite Fire Extinguisher – FX340SC-2

Part number 21006350P

Low & Moderate Hazard use

Single use

## UL Rated 3-A, 40-B:C



## Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

Model FX340SC-2 is fitted with a pressure gauge that provides at-a-glance status. The cylinder is manufactured from lightweight aluminum and it has a tough aluminum valve assembly.



Includes plastic wall hanger (293263).

## FOR LOW & MODERATE HAZARDS

A 3-A:40-B:C rated extinguisher is required for protecting both LOW & MODERATE hazard occupancies such as: living areas of the home, offices, churches, assembly halls, classrooms, hotel guest areas, home garage & workshop, light manufacturing, dining areas, auto showrooms, parking garages & storage areas.

For use on the following types of fire:



## Features

- Pressure gauge allows for immediate pressure status check
- Easy-to-pull safety pin
- Impact resistant metal valve, handle and lever
- 5.5 lb. of fire extinguishing agent (Average)
- 12 year limited warranty
- UL approved wall hanger
- Powder coated cylinder for corrosion protection



P/N: 21006350P - 4 pack  
 UPC: 0-47871-27053-8  
 IZF: 10047871270535

## Product Specification

Net agent weight (Average)	5.5 lb.
Unit weight (Average)	8.25 lb.
Diameter	4.5 inches
Height	16.8 inches
Discharge time	13-15 seconds
Discharge range	12-18 feet
Operating pressure	195 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Aluminum
Wall hanger	UL Listed

## Packaging Options



Packaging dimensions (inches)

	Depth	Width	Height
Carton	4.75	6.0	17.0
Master Pack	13.0	17.25	9.87



1016 Corporate Park Drive, Mebane, NC 27302

(800) 880-6788

www.Kidde.com

This information is subject to change without notice. Kidde Fire Safety disclaims any liability for any errors or misinterpretations of the information contained therein. Contact Kidde Fire Safety or your local distributor for assistance.