

DS-DP320F1-5V/C(30PCS)



- High reliability, strong load capacity, in line with 3C requirements
- 100% full load aging test
- Air natural convection cooling
- Protection functions include: short circuit/overload

▪ Specification

Cabinet	
Dimensions (W × H × D)	190 (W) mm × 81.6 (H) mm × 30 (D) mm (7.48" × 3.21" × 1.18")
Power	
Output Current	40A
Output Voltage	5V
Voltage Accuracy	±3%
Line Regulation	±0.5%
Load Regulation	±2.0%
Frequency Range	47 ~ 63HZ
Efficiency	87%
Short Circuit	Hiccup mode,auto-recovery
Power Factor	≥0.48
Inrush Current	50A/230VAC
Leakage Current	<1.5mA/230VAC
Rated Power	200W
Working Environment	
Working Temperature	-40 °C to 70 °C (-40 °F to 158 °F)
Working Humidity	10% RH to 95% RH (without condensation)
Storage Temperature	-40 ™ to 85 ™ (-40 ™ to 185 ™)
Storage Humidity	10% RH to 95% RH (without condensation)
General	
Weight	345g

▪ Available Model

DS-DP320F1-5V/C(30PCS)

See Far, Go Further



www.hikvision.com
support@hikvision.com

