

EM60 Color-screen Expansion Module

Fanvil EM60 is a multi-functional color-screen expansion module, sold separately as an accessory. It is compatible with V65/V66/V66 Pro IP phone and aims to provide efficient desktop solutions for staff dealing with heavy and diverse call workloads.

The EM60 comes with a large 4.3-inch color-screen, offering users a rich visual experience. It supports up to 60 programmable keys, with 20 keys per page and three-page switching. Each key is equipped with a dual-color LED indicator. When connected to a compatible phone, it enables various functions such as speed dialing, call forwarding, call transfer, call parking, and BLF status display.

Designed for high-frequency call scenarios, EM60 helps users handle large numbers of concurrent incoming calls with ease. This significantly enhances the user experience of IP phones and improves overall office efficiency.



4.3-inch color screen



USB



DSS key

Highlights

- ✓ The 4.3-inch 480x272 pixel color-screen greatly enriches the user's visual experience.
- ✓ The physical DSS keys on each page with dual-color LED.
- ✓ 3 independent control keys with illuminated LED are used for fast switching pages.
- ✓ USB connect, to ensure a higher reliability of data transmission and a higher speed of data refresh.
- ✓ Support up to 4 expansion modules in cascade, connected in series via USB interface.
- ✓ Stand with 2 adjustable angles of 40 and 45 degrees.

Generic

- 4.3-inch (480x272) color screen
- Color icons for a rich visual experience
- 20 physical DSS keys on each page with dual-color LED
- 3 independent control keys with illuminated LED are used for fast switching pages, three page views are possible
- Support up to 4 expansion modules in cascade, connected in series via USB interface.
- Desktop stand
- Stand with 2 adjustable angles of 40 and 45 degrees
- External power supply

Device Functions

- Screen saver
- User Defined DSS Keys
- Programmable for shared line, BLF List, call park, Intercom, conference, forward, group pickup, group listening, LDAP,

URL etc.

- 3 pages max
- 60 additional keys through page switch
- Support USB headset or USB BT dongle or USB Wi-Fi dongle or flash driver or Expansion Module, etc.USB peripherals.
- Cascade 1 and 2 units: last stage plus adapter; Cascade 3 and 4 units: in the 2nd and last stage plus adapter

Physical Specifications

- LCD: 4.3-inch (480x272) color screen
- Keypad: 23 keys, including
 - 20 DSS keys (With two-color LED light)
 - 3 Page-Switch (PS) keys (With two-color LED light)
- USB Cable x1
- Stand x1
- Connecting Sheet x1
- Screws x1
- DC port x1: $\Phi 5.5 \times 2.1 \times 10 \text{ mm}$
- Type-C port x1: Connects to the IP phone or cascaded EM60 expansion module
- USB2.0 port x1: Standard A

- Connect USB headsets, USB Dongles, USB flash drives, and cascading EM60 expansion consoles
- Power adapter x1: DC 5V / 1A
 - Input: 100-240VAC~50/60Hz 0.3A
 - Output: 5V/1A
- Power Consumption (use the power adapter): Idle 1.61W, Peak 2.72W
- Working temperature: 0°C~ 45°C
- Working humidity: 10%~95%
- Installation: Desktop stand
- Color: Dark Grey
- Qty/CTN: 20pcs
- N.W/CTN: 12kg
- G.W/CTN: 12.5kg
- Device Dimensions:
 - Desktop Stand (40°): 180.4*115*149.8 mm
 - Desktop Stand (45°): 170.3*115*158.1 mm
- Gift Box Dimensions: 285*121.5*52 mm
- Outer CTN Dimensions: 515*285*305 mm

The above specifications may be updated in the future without prior notice. All hardware/software/physical features should be based on the final shipped products.

