

USB-C to 2*HDMI(4K@60Hz)+DP+2*USB-A3.2+USB-C3.2+2*USB-A3.0+SD/TF+GigabitRJ45+3.5mm+PD(100W)

Specifications

- * Built-in Wire: Built-in wire is 25 cm long, conductor material: 34 AWG (7/0.06T), core material: tin-plated copper;
- * Input Port and Specifications
- ◆ 1xUSB-C male: a Complies with USB 3.2 standards and offers a transfer rate up to 10Gbps;
- b、 Supports DP1.4, HDCP2.3, with a maximum transmission rate of 8.1 Gbps per lane and a total bandwidth of 32.4 Gbps
- ◆ 1xPD Female: PD3.0, supports up to 100W charging and is backward compatible with PD2.0.
- * Output Ports and Specifications
- ◆ 2xUSB3.2A Female: A USB3.2 standard with a transfer rate up to 10Gbps, compatible with USB 3.0 and USB 2.0, supporting BC1.2 and connecting USB devices such as keyboards, mice, USB drives, and hard drives;
- ◆ 1xUSB3.2C Female: A USB3.2 standard with a transfer rate up to 10Gbps, compatible with USB 3.0 and USB 2.0, supporting BC1.2 and connecting USB devices such as keyboards, mice, USB drives, and hard drives;
- ◆ 2xUSB3.0A Female: USB3.0 standard, with a transfer rate up to 5Gbps, backward compatible with USB 2.0, does not support BC1.2, connecting keys, mice, USB drives, hard drives, etc.;
- ◆ 1xDP Female: DP1.4, HDCP2.3, supports resolutions up to 3840*2160@60Hz, backward compatible with 4K@30Hz, 2K@144Hz, 1080P@60Hz, etc.;
- ◆ 2xHDMI Female: HDMI 2.0, HDCP 2.3, supports resolutions up to 3840*2160@60Hz, and is backward compatible with 4K@30Hz, 2K@144Hz, 1080P@240/144Hz, 1080P@60Hz;
- ◆ 1xRJ45 Female: Gigabit network card with a maximum transmission rate of 1000 Mbps
- ◆ 1xSD Female: SD3.0, supports dual-SIM dual reading, with a maximum transfer speed of 104 MB/s;
- ◆ 1xTF Female: SD3.0, supports dual-SIM dual reading, with a maximum transfer speed of 104 MB/s;
- ◆ 1x3.5mm female: 4x3.5mm headphone jack, supports stereo audio output, microphone input, cable control, and hot swapping; supports national standard and American standard 4x3 headphones;
- * Power requirements: powered by the computer's USB-C port or PD.
- * Audio format: HDMI1/HDMI2/DP: DTS-HD/DTS/Dolby-AC3/DSD/HD (HBR)
- * Audio sampling rate: 3.5 mm/HDMI: supports up to 192 kHz/24 bits
- * Video display format
- Single Display: Win/Mac: HDMI/DP: Supports copy/extension modes with a maximum resolution of 4K@60Hz
- * Dual Displays: Win: Supports simultaneous display of any two screens (A+A+B) and dual-screen heterodyne displays (A+B: 4K@60Hz+C: 4K@60Hz). Mac: Supports mirror (A+A+A)/extended mode (A+B+B), does not support dual-screen heterodynex (A+B), with a maximum resolution of 4K@60Hz.
- * Supported Systems: Windows 11/10; linux; MAC OS;