

15550B/25036
30W 1C GaN Fast Charger

Specifications

- Color: 15550B Space Gray, 25036 Purple
- AC input: 100-240V~50/60Hz, 800mA Max
- USB Output:
- USB-C: 5V/3A 9V/3A 12V/2.5A 15V/2A 20V/1.5A 30W Max
- PPS: 3.3-11V/2.7A (2.7A is the product screen-printed label, measured at 3.3-11V/2.75A)
- Total Output Power: 30W Max
- Static power consumption $\leq 0.1W$
- Output ripple: 5V/9V $\leq 150mV$, 12V/15V/20V $\leq 200mV$
- USB-C Supported Protocols: PD3.0, PPS, QC4+(QC3.0/QC2.0), SCP(10V2.25A), FCP, AFC, APPLE 5V2.4A, Sumsung 5V2A, BC1.2
- Protection Types: Overcurrent/Overvoltage/Short-Circuit Protection, Overtemperature Protection (Overtemperature protection circuits integrated into the IC; output turns off at 150°C and returns to normal when below room temperature) * Indicator Light:/]
- Operating temperature: -10~25°C (safety test working environment temperature)
- Storage temperature: -20°C to 80°C
- Shell Material/Fire Resistance Rating: PC Material/ UL94-V0
- Application altitude ≤ 2000 meters

Selling points
