


## KS26, Split Bolt Connector, Run/Tap: #2 AWG-2/0 AWG Str

By Burndy  
Catalog # [KS26](#)



Copper Split Bolt, Cu: 2 AWG-2/0 AWG (Str) (Run & Tap)

### Features

- UL467 Listed for Direct Burial applications in earth or concrete
- Compact, high-strength, copper alloy with free-running threads and easy to grip wrench flats
- Highly resistant to cracking and corrosion

### Application

For Direct Burial Applications In Earth Or Concrete, Copper

### Specifications

Buy American Compliant	Yes
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	<ul style="list-style-type: none"> <li>• UL 486A</li> <li>• UL486B</li> </ul>
Buy America(n) Qualified	<ul style="list-style-type: none"> <li>• Buy America Compliant (All status valid till December 2025)</li> <li>• Buy American Act Compliant (All status valid till December 2025)</li> <li>• BABA Compliant (All status valid till December 2025)</li> </ul>
Certification - ETL	No
Standards - Industry Standards Met	<ul style="list-style-type: none"> <li>• UL 486A</li> <li>• UL486B</li> </ul>
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

### Conductor

Conductor - Rebar Size	3
Conductor - Rebar Size Range	3
Conductor - Copper Solid Run	3/0 AWG
Conductor - Copper Solid Run Range	2 AWG-2/0 AWG
Conductor - Copper Solid Tap	3/0 AWG
Conductor - Copper Solid Tap Range	14 AWG-2/0 AWG
Conductor - Copper Str Run	<ul style="list-style-type: none"> <li>• 2 AWG</li> </ul>

Conductor - Copper Str Run Range	<ul style="list-style-type: none"> <li>• 1 AWG</li> <li>• 1/0</li> <li>• 2/0 AWG</li> </ul>
Conductor - Copper Str Tap	<ul style="list-style-type: none"> <li>• 14 AWG</li> <li>• 12 AWG</li> <li>• 10 AWG</li> <li>• 9 AWG</li> <li>• 8 AWG</li> <li>• 7 AWG</li> <li>• 6 AWG</li> <li>• 5 AWG</li> <li>• 4 AWG</li> <li>• 3 AWG</li> <li>• 2 AWG</li> <li>• 1 AWG</li> <li>• 1/0</li> <li>• 2/0 AWG</li> </ul>
Conductor - Copper Str Tap Range	2 STR - 2/0 STR
Conductor Type	<ul style="list-style-type: none"> <li>• CU C Solid-Run</li> <li>• CU C Str-Run</li> <li>• CU Weld C Solid-Run</li> <li>• CU Weld C Str-Run</li> <li>• CU C Str-Tap</li> <li>• CU Weld C Solid-Tap</li> <li>• CU Weld C Str-Tap</li> <li>• CU C Solid-Tap</li> </ul>
Conductor - CopperWeld Solid Run	3/0
Conductor - CopperWeld Solid Run Range	3/0
Conductor - CopperWeld Solid Tap	3/0
Conductor - CopperWeld Solid Tap Range	3/0
Conductor - CopperWeld Str Run	7 #7
Conductor - CopperWeld Str Run Range	7 #7
Conductor - CopperWeld Str Tap	7 #7
Conductor - CopperWeld Str Tap Range	7 #7

### Configuration

Connector Type Split Bolt

### Dimensions

Dimension - L Length Overall mm	49 mm
Width	0.82 in
Dimension - Width fraction	41/50 in
Dimension - Width inch	0.82 in
Dimension - Width mm	21 mm
Dimension - B Length fraction	9/10 in
Dimension - B Length inch	.90 in
Dimension - Length Overall inch	1.94
Dimension - Cross Flats inch	1.05 in

### Force Related

Installation Torque	385 in
Recommended in-lb	

### General

Trade Name	SERVIT®
Sub Brand	SERVIT
Plated	N
Type	KS, Compact
UPC 12 Digit	781810013281
UPC 14 Digit GTIN	00781810013281
Material	Copper
Plating Type	Unplated
UPC	781810013281

### Logistics

Minimum Pack Quantity	1
Carton Quantity	25
Pallet Quantity	8700

### Product Assets

[Catalog \[English\]](#)



A Hubbell brand