



**EcoFlow Delta 3 2000 Air technical specifications:
EF-DL3-MA**

Product Name	Delta 3 2000 Air
Model	EF-DL3-MA
Dimensions (WxDxH)	220mm*223mm*426mm
Gross Weight	19.3±0.3Kg
Net Weight	17.5±0.3Kg
Ingress Protection Rating	IP30
Warranty Period	2 years
Appearance	PC/ABS in Dark Gray
Fire-proof	5VA
Monitoring Mode	LCD segmented display + indicator lights
Operating Temperature Range	Charging: 0~45°C(32~113°F) Discharging: -10~45°C(14~113°F)
Storage Temperature Range	-10~45°C(14~113°F)
Operating Humidity	10%~95% RH
Maximum Operating Altitude	3000m
Noise Emission	≤44dB
Maximum PV Input Power (W)	500W Max per port, total 1000W
Low-PV Input	PV Input: 12~60V=15A Max, 500W Max *2
Car input	Car input: 12-48V=8A Max, 384W Max *2
AC Input (Charge Only)	100-240V~50/60Hz 10A
AC Input (Bypass Mode)	100-120V~50/60Hz 10A
Maximum Rechargeable Voltage Range	85-290V
Bypass Overvoltage Protection Voltage	150V
Bypass Undervoltage Protection Voltage	80V
USB Output Port	USB-A (X2) 5V=2.4A 12W Max per port, total 24W USB-C (X2) 5V=3A/9V=2A/12V=1.5A 18W Max per port, total 36W
AC Output (Discharge Only)	120V~60Hz 1000W, Surge 2000W, X-Boost 1500W
AC Output (Bypass Mode)	100-120V~50/60Hz 1000W Max
AC Output (Grid-connected mode)	800W
UPS	10ms
Rated Capacity	1920Wh 19.2V=100Ah
Battery input port	16.8V~21.6V/55A
Battery output port	16.8V~21.6V/66A
Nominal Voltage (V)	19.2V
Cell Chemistry	LiFePO4



Protection Type	Over Voltage Protection, Overload Protection, Over Temperature Protection, Short Circuit Protection, Low Temperature Protection, Low Voltage Protection, Overcurrent Protection
Accessory List	All standard accessories: Warranty card, Safety instructions, Quick guide, Promotional card, AC power cord US Standard: US 3-prong plug + C13 power cord × 1.2 m