

# *UNITREE* Go2

New Creature of Embodied AI

New and Improved  
Returning with Glory

Infinite Revolution



# Standard Ultra-wide 4D LIDAR Upgrades Recognition System by 200%

Go2 features with Unitree's self-developed 4D LIDAR L1 with 360° x90° hemispherical ultra-wide recognition, super small blind spot and a minimum detection distance as low as 0.05m, which makes Go2 realize all-terrain recognizing.



**360°x90°**

Ultra-wide Scanning

**0.05m**

Blind Spot

(Radar accuracy decreases at close range detection)

**20m**

@90% Reflectivity

**21600 points/s**

Effective Frequency

**43200 points/s**

Frequency of Sample

**100Klux**

Anti-highlight Protection

# Your New Intelligent Friend

## Tracking Module

Remote-controlled or automatic tracking

## Front Camera

Image transmission Resolution 1280\*720  
FOV 120°  
Ultra wide angle lens deliver rich clarity

## Front Lamp

Brightly lights the way ahead

## Intercom Microphone

Effective communication with no scenario restrictions

## Self-retracting Strap

Easy to carry and load things

## Powerful Core

- Motion controller
- High-performance ARM processor
- Improved AI algorithm processor
- External ORIN NX/NANO

## Hardware Upgrade

- 3D LIDAR
- 4G ESIM Card
- WiFi6 with Dual-band
- Bluetooth 5.2


for stable connection and remote control

## Smart Battery

Standard 8000m Ah battery  
Long-endurance 15000m Ah battery  
Protection from over-temp, overcharge and short-circuit

## Foot Force Sensor

Receiving foot perception in real time



## 4D LiDAR L1

360°\*90° omnidirectional ultra-wide-angle scanning allows automatic avoidance with small blind spot and stable operation

## 12 Knee Joint Motors

Strong and powerful  
Beautiful and simple  
Brandy new visual experience

## Speaker for Music Play

listen to music as your pleasure


# New Intelligence——Unitree Go2



## Intelligent Side-follow System 2.0

By adopting the new wireless vector positioning and control technology, the positioning accuracy is technically upgraded by 50%, the remote control distance is over 30m<sup>[1]</sup>, and combined with the optimised obstacle avoidance strategy, it can make the robot better traverse complex terrain.

[1] In open spaces with no shelter



## Motor performance enhanced by 30%

Go2 boasts a peak joint torque of 45N.m<sup>[2]</sup>, a new internal trace connecting technique, and heat pipe coolers to decrease temperature effectively.

[2] The maximum torque in the table refers to the maximum torque of the largest joint motor; the actual maximum torque varies for the 12 joint motors.



## Battery capacity and endurance upgraded by 150%

Go2 is equipped with a battery capacity increased to 8,000mAh, as a 15,000mAh ultra-long life battery is optional, and a voltage increased to 28.8V to improve motor efficiency, power and stability.




## Various actions and poses

Go2 boasts a variety of poses such as jumping, stretching, shaking hands, cheering, pouncing, and sitting down.


# Intelligent Interaction

Have great fun with the APP




## Intelligent Avoidance Precise and Agile

Equipped with 4D LiDAR L1, the robodog detects, captures and draws the 3D real world for user.



## Graphical Programming Simple Yet Smarter

Optimise the graphical programming function, make it easy to complete the program design by simple drag, drop and connection. Make programming beginners easy to start and innovate.



## Hd Picture Quality Real-time and Stable [1]

A new App realizes HD image transmission and real-time remote monitor. Built-in 4G and eSIM enables more stable connection and remote control.

[1] Transformation and quality varies considerably in different network environments.



## OTA Upgrades

Keep Improving and Evolving to be Smarter

With user authorisation, the robot automatically connects to a cloud-based OTA service to upgrade its own programs to continuously improve the user experience.



# Parameters

Mechanical & Electron	Type	AIR	PRO	EDU
	Stand Height	70×31×40cm		
	Weight (With Battery)	About 15kg		
	Material	Aluminium alloy + High strength engineering plastic		
	Voltage	28V~33.6V		
	Peaking Capacity	About 3000W		
Performance	Payload	≈7kg (MAX ~ 10kg)	≈8kg (MAX ~ 10kg)	≈8kg (MAX ~ 12kg)
	Speed	0~2.5m/s	0~3.5m/s	0~3.7m/s (MAX~5m/s)
	Max Climb Drop Height	About 15cm	About 16cm	
	Max Climb Angle	30°	40°	
	Basic Computing Power	○	8-core High-performance CPU	
Joint	Peak Joint Torque [1]	○	About 45N.m	
	Range of Motion	Body: -48~48°	Thigh: -200°~90°	Shank: -156°~-48°
	Intra-joint Circuit (knee)	●	●	●
	Joint Heat Pipe Cooler	●	●	●
Force Sensor	Super-wide-angle 3D LIDAR	●	●	●
	Wireless Vector Positioning Tracking Module	○	●	●
	HD Wide-angle Camera	●	●	●
	Foot-end Force Sensor	○	○	●
Feature List	Basic Action	●	●	●
	Auto-scaling Strap	○	●	○
	OTA Upgrades	●	●	●
	RTT2.0 Image Transmission	●	●	●
	Graphical Programme	●	●	●
	Front Lamp	●	●	●
	WiFi6 with Dual-band	●	●	●
	Bluetooth 5.2/4.2/2.1	●	●	●
	4G	○	●	●
	Voice Function [2]	○	●	●
	ISS 2.0	○	●	●
	Intelligent Detection and Avoidance	●	●	●
	Charging Pile Compatibility	○	○	●
	Secondary Development [3]	○	○	●
Accessories	Handheld Controller	Optional		Standard
	Docking Station	○		Optional Nvidia Jetson Orin
	Smart Battery	Standard (8000mAh)		Long endurance (15000mAh)
	Endurance	About 1-2h		About 2-4h
	Charger	Standard (33.6V 3.5A)		Fast charge (33.6V 9A)

※The above parameters may vary in different scenarios and configurations, please subject to actual situations.  
If any change in the appearance of the product, please refer to the actual product.

※ This product is a civilian robot. We kindly request that all users refrain from making any dangerous modifications or using the robot in a hazardous manner.

[1] The maximum torque in the table refers to the maximum torque of the largest joint motor; the actual maximum torque varies for the 12 joint motors.

[2] Voice functions include offline voice interaction, commands, intercom and music play.

[3] For more information, please read the secondary development manual.