



Figure similar

SIMATIC S7-1200, Digital I/O SM 1223, 16 DI/16 DO, 16 DI 24 V DC, Sink/Source, 16 DO, transistor 0.5 A

General information	
Product type designation	SM 1223, DI 16x24 V DC, DQ 16x24 V DC
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
from backplane bus 5 V DC, max.	185 mA
Digital inputs	
<ul style="list-style-type: none"> <li>from load voltage L+ (without load), max.</li> </ul>	4 mA; per channel
Output voltage	
Power supply to the transmitters	
<ul style="list-style-type: none"> <li>present</li> </ul>	Yes
Power loss	
Power loss, typ.	4.5 W
Digital inputs	
Number of digital inputs	16
<ul style="list-style-type: none"> <li>in groups of</li> </ul>	2
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Number of simultaneously controllable inputs	
all mounting positions	
<ul style="list-style-type: none"> <li>— up to 40 °C, max.</li> </ul>	16
horizontal installation	
<ul style="list-style-type: none"> <li>— up to 40 °C, max.</li> <li>— up to 50 °C, max.</li> </ul>	16
vertical installation	
<ul style="list-style-type: none"> <li>— up to 40 °C, max.</li> </ul>	16
Input voltage	
<ul style="list-style-type: none"> <li>Rated value (DC)</li> <li>for signal "0"</li> <li>for signal "1"</li> </ul>	24 V 5 V DC at 1 mA 15 V DC at 2.5 mA
Input current	
<ul style="list-style-type: none"> <li>for signal "0", max. (permissible quiescent current)</li> <li>for signal "1", min.</li> <li>for signal "1", typ.</li> </ul>	1 mA 2.5 mA 4 mA

<b>Input delay (for rated value of input voltage)</b>	
for standard inputs	
— parameterizable	Yes; 0.2 ms, 0.4 ms, 0.8 ms, 1.6 ms, 3.2 ms, 6.4 ms and 12.8 ms, selectable in groups of four
for interrupt inputs	
— parameterizable	Yes
<b>Cable length</b>	
• shielded, max.	500 m
• unshielded, max.	300 m
<b>Digital outputs</b>	
Number of digital outputs	16
• in groups of	1
Short-circuit protection	No; to be provided externally
Limitation of inductive shutdown voltage to	L+ (-48 V)
<b>Switching capacity of the outputs</b>	
• with resistive load, max.	0.5 A
• on lamp load, max.	5 W
<b>Output voltage</b>	
• Rated value (DC)	24 V
• for signal "0", max.	0.1 V; with 10 kOhm load
• for signal "1", min.	20 V DC
<b>Output current</b>	
• for signal "1" rated value	0.5 A
• for signal "1" permissible range, max.	0.5 A
• for signal "0" residual current, max.	10 µA
<b>Output delay with resistive load</b>	
• "0" to "1", max.	50 µs
• "1" to "0", max.	200 µs
<b>Total current of the outputs (per group)</b>	
horizontal installation	
— up to 50 °C, max.	8 A; Current per mass
<b>Relay outputs</b>	
Switching capacity of contacts	
— with inductive load, max.	0.5 A
— on lamp load, max.	5 W
— with resistive load, max.	0.5 A
<b>Cable length</b>	
• shielded, max.	500 m
• unshielded, max.	150 m
<b>Interrupts/diagnostics/status information</b>	
<b>Alarms</b>	
• Diagnostic alarm	Yes
<b>Diagnostics indication LED</b>	
• for status of the inputs	Yes
• for status of the outputs	Yes
<b>Potential separation</b>	
Potential separation digital inputs	
• between the channels, in groups of	2
Potential separation digital outputs	
• between the channels, in groups of	1
• between the channels and backplane bus	500 V AC
<b>Degree and class of protection</b>	
IP degree of protection	IP20
<b>Standards, approvals, certificates</b>	
CE mark	Yes
CSA approval	Yes
UL approval	Yes
cULus	Yes
FM approval	Yes

RCM (formerly C-TICK)	Yes	
KC approval	Yes	
Marine approval	Yes	
<b>Ecological footprint</b>		
• environmental product declaration	Yes	
<b>Global warming potential</b>		
— global warming potential, (total) [CO2 eq]	123 kg	
— global warming potential, (during production) [CO2 eq]	12.1 kg	
— global warming potential, (during operation) [CO2 eq]	111 kg	
— global warming potential, (after end of life cycle) [CO2 eq]	-0.434 kg	
<b>Ambient conditions</b>		
<b>Free fall</b>		
• Fall height, max.	0.3 m; five times, in product package	
<b>Ambient temperature during operation</b>		
• min.	-20 °C	
• max.	60 °C	
• horizontal installation, min.	-20 °C	
• horizontal installation, max.	60 °C	
• vertical installation, min.	-20 °C	
• vertical installation, max.	50 °C	
• permissible temperature change	5°C to 55°C, 3°C / minute	
<b>Ambient temperature during storage/transportation</b>		
• min.	-40 °C	
• max.	70 °C	
<b>Air pressure acc. to IEC 60068-2-13</b>		
• Storage/transport, min.	660 hPa	
• Storage/transport, max.	1 080 hPa	
<b>Relative humidity</b>		
• Operation at 25 °C without condensation, max.	95 %	
<b>Connection method</b>		
required front connector	Yes	
<b>Mechanics/material</b>		
Enclosure material (front)		
• Plastic	Yes	
<b>Dimensions</b>		
Width	70 mm	
Height	100 mm	
Depth	75 mm	
<b>Weights</b>		
Weight, approx.	310 g	
<b>Classifications</b>		
	<b>Version</b>	<b>Classification</b>
eClass	14	27-24-22-04
eClass	12	27-24-22-04
eClass	9.1	27-24-22-04
eClass	9	27-24-22-04
eClass	8	27-24-22-04
eClass	7.1	27-24-22-04
eClass	6	27-24-22-04
ETIM	10	EC001419
ETIM	9	EC001419
ETIM	8	EC001419
ETIM	7	EC001419
IDEA	4	3566

## Approvals / Certificates

## General Product Approval



[Manufacturer Declaration](#)



## General Product Approval

## For use in hazardous locations



[FM](#)

[CCC-Ex](#)



## For use in hazardous locations

## Maritime application

[Type Examination Certificate](#)



[Miscellaneous](#)

[CCC-Ex](#)



## Maritime application



[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)

## Maritime application

## Environment

[KR \(Korean Register of Shipping\)](#)



Siemens  
EcoTech



last modified:

4/6/2025