

WET CHEMICAL

6L WET CHEMICAL FIRE EXTINGUISHER

MODEL: WC6L

STANDARD COMPLIED WITH: ANSI/UL8



FEATURES:

Suitable for Class A and K Fires
Plated Brass Valve with Stainless Steel Handles
Stainless Steel Cylinder
100% Helium Leak Tested
Production Under ISO9001 Quality System



TECHNICAL SPECIFICATION

Model Number	WC6L
Capacity(gal/l)	1.6(6)
Cylinder Diameter(in/mm)	7.07(179.5)
Height(in/mm)	19.30(490)
Width(in/mm)	9.65(245)
Discharge Time(s)	51
Fire Rating	1-A:K
Extinguisher Weight(lb/kg)	21.56(9.78)
Packing Size(L×W×H)(in/mm)	7.48×7.48×19.88(190×190×505)
Working Pressure(psi/bar)	100(6.9)
Discharge Range(ft/m)	10-12(3-3.6)
Operation Temperature(F/C)	40~120(4~49)
UL list File Number	EX 28016
Marine Type	/
USCG Approval Number	/

* Transport Classification: Non-Flammable, Non-Toxic Gas.
UN No.1044 Class 2.2

Valve		024313004
Seal		0714025
Lever		0202118
Rivet		0204029
Carry Handle		0203089
Valve Body		020504045
Bracket		070200007
		070200010
		070100016
Screw		0715038
Hanging Loop		0715037
Hose Assembly		080100093
Cylinder		0501000244
Safety Pin		020901003
		020901033
Chain		0210001
Pressure Gauge		040332
Valve Stem Assembly		Electroplate 0220148
O Ring		020603009
Spring		020701040
Ring Nut		0234004
Dip Tube Assembly		080408005
Anti-overfill Tube		2012029
Strap		071118
Hose Catch		071007