



C-U32/FF

USB 3.2 GEN-2 Full Featured USB-C (M) to
USB-C (M) Cable

| 4K/60 UHD (4:4:4)



C-U32/FF is a USB-C(M) to USB-C(M), USB 3.2 Gen-2 SuperSpeed+ cable offering a whole new level of reliable connectivity thanks to kramer's unique K-lock. Transfer Video 4K@60 data at incredible speeds (10G), charge other devices (100W), and even power mobile devices – all with just one passive cable.

C-U32/FF offers throughput of up to 10Gbps when used with a USB 3.2 host and device. The symmetrical, low profile USB Type-C connector, with the integrated K-Lock mechanism, can be plugged in any direction, thus eliminating the frustration of getting the port insertion just right

FEATURES

Quality Construction - High-quality shielded twisted pair (STP) construction helps prevent electromagnetic interference and ensures reliable data communication

Reversible USB Type-C Connector with integrated locking mechanism

Transfer Rates - Up to 10Gbps

100W power (5A, 20V)

PC, Mac & Mobile Compatible

Plug and Play - For monitors, Web cameras, printers, scanners, keyboards and other digital devices

USB Backward Compatibility - 1.0, 1.1, 2.0 and 3.0

Logo on mold as orientation mark - See the [Why USB-C Is More Than Just a Connector: Understanding Directionality](#) article in the Resources tab

RoHS REACH Compliant



TECHNICAL SPECIFICATIONS

TOTAL	Type: USB 3.2 GEN-2 Video 4K@60 4:4:4 (DP Alt Mode) Max. Data Rate: 10Gbps ETH Support: 10/100/1000 Mbps
PHYSICAL	Connector A: USB Type-C Male Nickel plated K-Lock connector with gold pins Connector A Length x Width x Height: 23x12x8mm Connector B: USB Type-C Male Nickel plated K-Lock connector with gold pins Connector B Length x Width x Height: 23x12x8mm
CONDUCTORS	Tinned Copper/Bare Copper 24/30/32AWG
SCREENING	Triple shielding (Aluminum-Mylar foil with braid)
JACKET	Material: PVC Color: Black Diameter 4.8mm $\pm$ 0.2mm Bending Radius: 25.4mm
ELÉCTRICA	Temperature Rating: 80°C Voltage Rating: 30V Conductor Resistance – 32AWG: 588 Ω /km MAX. at 20°C (68°F) Conductor Resistance – 30AWG: 376 Ω /km MAX. at 20°C (68°F) Conductor Resistance – 24AWG: 94.2 Ω /km MAX. at 20°C (68°F)
STANDARDS COMPLIANCE	Safety: CE, FCC Flammability Rating: VW-1



CONFIGURATIONS

C-U32/FF-3	USB 3.2 GEN-2 Full Featured USB-C (M) to USB-C (M) Cable: Passive Cable Length — 3ft (0.9m)
C-U32/FF-6	USB 3.2 GEN-2 Full Featured USB-C (M) to USB-C (M): Passive Cable Length — 6ft (1.8m)
