

## DS-PT1-WB



- 433MHz two-way wireless communication
- AES-128 encryption
- LED display, show the different feedbacks with easy understanding
- Operation: Stay arm/away arm/disarm by areas
- Arming process with fault confirm, more secure
- Patrol tag check in
- Front and rear panel tamper-proof

## ▪ Specification

| Hardware features          |   |
|----------------------------|---|
| Power switch               | Power on/off  |
| Electrical characteristics |   |
| Battery type               | Three AA batteries  |
| Operation humidity         | 10% to 90% (no condensing)  |
| Operation temperature      | -10°C to +55°C (-4°F to +122°F)   |
| Power consumption          | Quiescent current: 110 uA<br>Max current: 292mA<br>Voltage: 1.5 VDC                   |
| Battery life span          | Up to 2 years (standby time)  |
| Wireless transmission      |   |
| RF frequency               | 433 MHz   |
| RF modulation              | 2GFSK   |
| Display                    |   |
| Indicator                  | 5, area(blue), fault(orange), arm(blue), disarm(green), alarm(red), signal(red/green) |
| General                    |   |
| Installation method        | Wall mounting   |
| Dimension(WxHxD)           | 75*124*21 mm  |
| Color                      | white   |
| Weight                     | 176g (with battery)   |

## ▪ Available Model

DS-PT1-WB

**Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
www.hikvision.com



Follow us on social media to get the latest product and solution information.

